



## VHF AND UHF TRANSCEIVERS

# IC-F3032T

VHF transceiver with full keypad

# IC-F4032T

UHF transceiver with full keypad

# IC-F3032S

VHF transceiver with simple keypad

# IC-F4032S

UHF transceiver with simple keypad

## Superior Waterproof Protection Combined with Versatile Functions



### IP67 waterproof and dust-tight protection

The IC-F3032T/S series can withstand 1 m depth of water for 30 minutes and its dust-tight construction that prevents the ingress of powder dust, sand, mud and other objects.

### Longer operating time

The supplied waterproof Li-ion battery pack, BP-232WP (7.4 V, 2350 mAh (typ.)), provides 17.5 hours\* of operating time. The battery has been designed for reliability in extremely cold environments.

\*Tx:Rx:Standby=5:5:90. Power save function ON.

### Selective calling, quiet stand-by and more

The IC-F3032T/S series has built-in 2-Tone, 5-Tone, CTCSS and DTCS signaling capabilities for group communication or selective calling. When a matched 2-Tone/5-Tone is received, the following actions are programmable for each code.

- Answer back calls • Beep sounds • Bell icon
- Radio stun/kill/revive • Auto TX • Scan

### MDC 1200 compatible

The following selective calling and ANI features are programmable with the built-in MDC signaling.

- PTT ID • Emergency (No ACK transmission)
- Radio check (RX only) • Stun/Revive (RX only)

### Emergency function

A red button on the top panel can be used as an emergency button and can be used to transmit an emergency signal. Man down (optional UT-124R required) and lone worker functions can also be used for the emergency function trigger.

### Scan features

Priority scan allows you to monitor one or two priority channels while scanning other channels. The mode dependent scan automatically changes the scanning list following the operating channel. The Tx channel and talk back functions allow you to make a quick response while scanning.

### Internal option units available

The IC-F3032T/S series has an internal socket for a variety of option units including voice scrambler, DTMF decoder or man down unit.


### Other features

- Up to 128 memory channel with 8 zones
- 8-character alphanumeric LCD
- 8 DTMF autodial memories
- Optional HM-168LWP, waterproof speaker-mic
- BIIS PTT ID transmission
- Low battery alert
- 2-step power save
- PC programmable
- Time out timer
- Talk around function
- Surveillance function



IC-F4032T

IC-F3032S



Limited functions.

**SPECIFICATIONS**

	IC-F3032T/S	IC-F4032T/S
<b>GENERAL</b>		
Frequency coverage	136–174 MHz	400–470 MHz
Number of channels	128 channels/8 zones	
Type of emission	16K0F3E/14K0F3E/8K50F3E	
Channel spacing	25/20/12.5 kHz	
Power supply requirement	7.2 V DC nominal	
Current drain (approximate)		
Tx High	1.5 A (at 5 W)	1.6 A (at 4 W)
Rx Max. audio/Standby	250 mA/75 mA	300 mA/75 mA
Antenna impedance	50 Ω	
Operating temperature range	–25 °C to +55 °C (Radio specifications)	
Dimensions (W × H × D) (Projections not included)	53 × 120 × 37 mm (With BP-232WP)	
Weight (approximate)	310 g (With BP-232WP)	
<b>TRANSMITTER</b>		
Output power (at 7.2 V DC)	5 W, 2 W, 1 W (Hi, L2, L1)	4 W, 2 W, 1 W (Hi, L2, L1)
Max. frequency deviation	±5.0/±4.0/±2.5 kHz (Wide/Middle/Narrow)	
Frequency stability	±2.5 ppm	
Spurious emissions	0.25 μW (≤ 1 GHz), 1.0 μW (> 1 GHz)	
Residual modulations	53/51/48 dB typ. (Wide/Middle/Narrow)	55/53/50 dB typ. (Wide/Middle/Narrow)
Audio harmonic distortion	3% typ. (AF 1 kHz 40% deviation)	
Ext. microphone connector	3-conductor 2.5 (d) mm (1/8")/2.2 kΩ	
<b>RECEIVER</b>		
Sensitivity (at 20 dB SINAD)	–4 dBμV typ. emf	
Adjacent channel selectivity	75/75/65 dB typ. (Wide/Middle/Narrow)	75/73/65 dB typ. (Wide/Middle/Narrow)
Spurious response rejection	70 dB min.	
Intermodulation rejection	67 dB typ.	
Hum and noise (With CCITT filter)	60/58/55 dB typ. (Wide/Middle/Narrow)	55/53/50 dB typ. (Wide/Middle/Narrow)
Audio output power	500 mW typ. (at 5% distortion, 8 Ω load)	
Ext. speaker connector	2-conductor 3.5 (d) mm (1/8")/8 Ω	

Measurements made in accordance with EN 300-086.  
All stated specifications are subject to change without notice or obligation.

**Applicable U.S. Military Specifications & IP Rating**

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

<b>Ingress Protection Standard</b> (IC-F3032T/S, F4032T/S, BP-232WP and HM-168LWP)	IP67 (Dust-tight and waterproof protection)
--	---

<b>Supplied accessories:</b> (May differ according to version)
• Battery pack, BP-232WP    • Belt clip, MB-94    • Antenna

**OPTIONS**

Some options may not be available in some countries. Please ask your dealer for details.

**BATTERY PACK AND CASES**

BP-232WP    BP-240    BP-261

Battery packs and cases	Type	Capacity	Operating time*
BP-232WP	Rechargeable Li-ion	2200 mAh (min.) 2350 mAh (typ.)	17.5 hours (Approx.)
BP-240	LR03 (AAA) batteries × 6	–	–
BP-261	LR6 (AA) batteries × 6	–	–

\* Tx: Rx: standby = 5:5:90. Power save function ON.

**REGULAR CHARGER**

BC-171  
BC-147S\*1

Charges the BP-232WP in 8–10 hours (approx.).

**RAPID CHARGER**

BC-123S\*1    BC-160

Charges the BP-232WP in 3 hours (approx.).

**MULTI-CHARGER**

BC-197\*2

Charges up to six BP-232WP battery packs in 3.5 hours (approx.).

\*1 BC-123/BC-147SA for USA plug. SE for Europe plug. SV for Australia plug. BC-123SUK for UK.  
\*2 AD-122 charger adapter is supplied with the BC-197, depending on version.

**SPEAKER-MICROPHONES**

HM-168LWP    HM-158LA    HM-159LA

**EARPHONE-MICROPHONES**

HM-153LA    HM-166LA

**HEADSETS and PTT SWITCH CABLE**

HS-94    HS-95    HS-97    VS-4LA

Earhook type    Behind-the-head type    Throat type    Required when using any of these headsets

**CHARGER BRACKET**

MB-130

For use with BC-160.

**EARPHONE**

SP-27

Tube earphone

**LEATHER BELT HANGERS**

MB-96N    MB-96F    MB-96FL

Swivel type    Fixed type    Long type

**BELT CLIPS**

MB-93    MB-94

Swivel type    Alligator type

**CIGARETTE LIGHTER CABLE**

CP-23L

For use with BC-160

**POWER SUPPLY CABLE**

OPC-656

For use with BC-197

**INTERNAL UNITS**

UT-109R    UT-110R    UT-124R

Non-rolling voice scrambler    Rolling voice scrambler    Man down unit

**ANTENNAS**

- FA-SC25V: 136–150 MHz
- FA-SC55V: 150–174 MHz
- FA-SC25U: 400–430 MHz
- FA-SC57U: 430–470 MHz

**STUBBY ANTENNAS**

- FA-SC56VS: 150–162 MHz
- FA-SC57VS: 160–174 MHz
- FA-SC73US: 450–490 MHz

**CUT ANTENNAS**

- FA-SC61VC: 136–174 MHz
- FA-SC61UC: 380–520 MHz

**HIGH GAIN ANTENNAS**

- FA-SC62V: 150–160 MHz
- FA-SC63V: 155–165 MHz

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. All trademarks are the properties of their respective holders.

**Icom Inc.** 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 [www.icom.co.jp/world](http://www.icom.co.jp/world) **Count on us!**

**Icom America Inc.**  
[www.icomamerica.com](http://www.icomamerica.com)

**Icom (Europe) GmbH**  
[www.icomeurope.com](http://www.icomeurope.com)

**Icom (Australia) Pty. Ltd.**  
[www.icom.net.au](http://www.icom.net.au)

Your local distributor/dealer:

**Icom Canada**  
[www.icomcanada.com](http://www.icomcanada.com)

**Icom Spain S.L.**  
[www.icomspain.com](http://www.icomspain.com)

**Shanghai Icom Ltd.**  
[www.bjicom.com](http://www.bjicom.com)

**Icom Brazil**  
E-mail: [sales@icombrasil.com](mailto:sales@icombrasil.com)

**Icom (UK) Ltd.**  
[www.icomuk.co.uk](http://www.icomuk.co.uk)

**Icom France s.a.s.**  
[www.icom-france.com](http://www.icom-france.com)